



COMHAIRLE CONTAE  
CHEATHARLACH  
CARLOW COUNTY COUNCIL

**SECTION 75 ROADS ACT 1993  
S.I. No. 119/1994 ROADS REGULATIONS 1994**

**TEMPORARY CLOSURE OF ROADS  
NOTICE OF INTENTION**

**ROAD: L-7112 - RATHOE, CO. CARLOW**

Carlow County Council wishes to give notice of its intention to temporarily close the above road between Rathoe Road and Ardbearn Cross to facilitate Kendra Civil Engineering Ireland Ltd in carrying out essential maintenance works for the grid connection from the Garreenleen Solar Farm Substation to the ESB substation at Kellis.

**Dates of Closure: 19<sup>th</sup> May 2025 – 29<sup>th</sup> June 2025                      From: 24-hr                      To: 24-hr**

**Diversions and Alternative Routes will be signposted. A map of the above routes is available to view on our website at [www.carlow.ie](http://www.carlow.ie) under Statutory Notices.**

Submissions regarding this temporary road closure may be made in writing and/or via e-mail to the **Senior Engineer**, Transportation Department, Carlow County Council, Athy Road, Carlow ([seniorengineer@carlowcoco.ie](mailto:seniorengineer@carlowcoco.ie)) to be received **no later than 17:00 hrs on Thursday, 17<sup>th</sup> April 2025.**

**Pádraig O’Gorman,  
Director of Services.**

Rev:	00
Description:	ESB Connection
Date:	04/10/2024

Job Details:	Garraheen Solar Farm - 110KV Grid Route
Sheet:	1 of 1

Drawing:	Traffic Management details - L7112, Road Closure Between Junction of Rathoe Rd and Ardbeam. (52.77421304623327, -6.81637157573759)
Date:	04/12/2024
Drawn by:	DL - Plan
Rev:	00
Scale:	N.T.S



© 2024 Microsoft Corporation © 2024 Maxar © CNES

**Legend**

- Wedge Zone
- Dimension Route
- Traffic Cone
- Cone marked sign
- Clear Section of Road
- Longitudinal Safety Zone
- Chowen Bar
- Cone marked sign

**Parameters:**

- Local road speed - 80km/h
- Distance between Advance signs - 200m
- No. of Advance signs - 4
- Min. Visibility of signs - 120m
- Longitudinal Safety Zone - 60m
- Lateral Safety Zone - 1.2m
- Lead in Taper - 45 degree
- Max. at Taper cone spacing - 3m
- Max longitudinal cone spacing - 12m.
- Traffic Flow is Road Closure with Diversion

**Notes:**

- All signs to comply with Chapter 8
- Exact sign positions to be agreed on site.
- Safety zones to be maintained at all times.
- Signs to be positioned so as not to obstruct other road users.
- Min. Line width to be maintained at 3m at all times, 3.25m where possible.
- End of Road Works signs to be placed within 20m of works area end.
- Existing Signage to be covered whilst TM in operation.
- Marshals at both end of Road Closure.