



COMHAIRLE CONTAE
CHEATHARLACH
CARLOW COUNTY COUNCIL

**SECTION 75 ROADS ACT 1993
S.I. No. 119/1994 ROADS REGULATIONS 1994**

**TEMPORARY CLOSURE OF ROADS
NOTICE OF DECISION**

ROAD: L3053 - BETWEEN KELLIS LANE & RATHOE ROAD, CO. CARLOW

Carlow County Council having given the required notice intend to temporarily close the above road between Kellis Lane and Rathoe Road to facilitate Kendra Civil Engineering Ireland Ltd in carrying out essential maintenance works for the grid connection from the Garreenleen Solar Farm Substation to the ESB substation at Kellis.

Dates of Closure: 30th June 2025 – 19th September 2025 From: 08:00 To: 18:00

Diversions and Alternative Routes will be signposted. A map of the above routes is available to view on our website at www.carlow.ie under Statutory Notices.

**Pádraig O’Gorman,
Director of Services.**

| | | |
|---------|-----------------------------|------------------|
| Rev: 00 | Description: ESB Connection | Date: 04/12/2024 |
|---------|-----------------------------|------------------|

| | |
|--------------|---|
| Job Details: | Serrinleen Sollar Farm - 110KV Grid Route |
| Sheet: | 1 of 1 |

| | | |
|----------|---|------------------|
| Drawing: | Traffic Rearrangement details - L11025IL3033, Road Closure Between Junction of Kells Lane(L3033S3) and Rathoe Rd. (62,78,79,80, -6,52,2705) | Date: 04/12/2024 |
| Rev: 00 | Dwg no: 01 - Plan | Scale: N.T.S |



Legend

- Work Zone
- Diversion Route
- Traffic Cone
- Lateral Safety Area
- Longitudinal Safety Area
- Closure Barrier
- Cone mounted sign

- Parameters:**
1. Local road speed - 80km/h
 2. Distance between Advance signs - 200m
 3. No. of Advance signs - 4
 4. Min. Visibility of signs - 120m
 5. Longitudinal Safety zone - 60m
 6. Lateral Safety zone - 12m
 7. Lead in Taper - 45 degrees
 8. Max. at taper cone spacing - 3m
 9. Max longitudinal cone spacing - 12m
 10. Traffic Flow is Road Closure with Diversion

- Notes:**
1. All signs to comply with Chapter 8
 2. Exact sign positions to be agreed on-site.
 3. Safety zones to maintained at all times to be positioned so as not to obstruct approved use.
 4. Mfn. Lane width to be maintained at 3m at all times. 3.25m where possible.
 5. End of Road Works signs to be placed within 20m of works area and
 6. Existing Signage to be covered whilst TM in operation.
 7. Marshall at both end of Road Closure.