



**COMHAIRLE CONTAE
CHEATHARLACH**
CARLOW COUNTY COUNCIL

**SECTION 75 ROADS ACT 1993
S.I. No. 119/1994 ROADS REGULATIONS 1994**

**TEMPORARY CLOSURE OF ROADS
NOTICE OF DECISION**

BROWNESHILL ROAD, CARLOW TOWN L-4016-0

Carlow County Council having given the required notice intend to temporarily close the road listed hereunder to facilitate Ward and Burke in carrying out essential wastewater works.

Road to be Closed:

Browneshill Road, Carlow Town L-4016-0

Dates of Closure:

29th June 2026 – 3rd July 2026

Times of Closure:

From: 8:00hrs

To: 18:00hrs (daily)

Diversions and Alternative Routes will be signposted. A Map of the above route is available to view on our website at www.carlow.ie under Statutory Notices.

**Pádraig O’Gorman,
Director of Services.**

COPYRIGHT: This drawing is protected by copyright and may not be reproduced in any form without the prior written consent of Invarion.

- NOTES:**
1. DRAWING NOT TO SCALE
 2. STOP AND GO TRAFFIC MANAGEMENT SYSTEM WILL BE IN PLACE.
 3. ALL TRAFFIC SIGNS TO BE REFLECTIVE AND IN ACCORDANCE WITH CHAPTER 8.
 4. ALL TRAFFIC CONES SHALL CONFORM TO BE E11302 300-HAND HAVE A REFLECTIVE SURFACE.
 5. EXACT SIGN POSITION WILL BE AGREED ON SITE
 6. THE PLAN MAY ONLY BE IMPLEMENTED BY A QUALIFIED CCAS & G OPERATIVE
 7. PEDESTRIAN BARRIERS TO BE ERECTED ALONG WORKS TO PREVENTS PUBLIC ACCESS TO WORK SITE.
 8. WORKS TO BE CARRIED OUT IN ACCORDANCE WITH ALL RELEVANT AUTHORITIES AND CONTRACT REQUIREMENTS.

- LEGEND:**
- WORKS ZONE
 - SAFETY ZONE
 - TRAFFIC CONES
 - PEDESTRIAN BARRIER
 - ROAD CLOSED
 - DIVERSION ROUTE
 - DIVERSION ROUTE

TRAFFIC MANAGEMENT PARAMETERS

TRAFFIC MANAGEMENT PARAMETERS	MINIMUM 1 (M)	MINIMUM 2 (M)
ROAD CLASSIFICATION	A	A
ROADWORKS TYPE	1	1
STREET LIMIT (MM)	50	50
NO. OF SIGNS	2	2
CONE SPACING (M)	5	5
CONTRACT LENGTH (M) (MIN)	50	50
MINIMUM CLEARANCE (M)	25	25
MINIMUM CLEARANCE (M) (MAX)	60000	60000
SIZE OF ROADWORKS SIGN (M)	60000	60000
SIZE OF CIRCULAR WARNING SIGN (M)	60000	60000
HEIGHT OF SIGNS (M)	2.0	2.0
MINIMUM CLEARANCE (M)	3	3
LONGITUDINAL SAFETY ZONE (M)	5	5
LATERAL SAFETY ZONE (M)	0.5	0.5
CONE SPACING		
AT TAPER (M)	3	3
LONGITUDINAL (M)	3	3
MINIMUM CONE HEIGHT (MM)	750	750
MINIMUM RATE OF TAPER		
UPPER LANE (M)	1 IN 5	1 IN 5
LOWER LANE (M)	1 IN 5	1 IN 5

REV	DATE	DESCRIPTION	DRN	CHK	APP
000	28/02/2016	INITIAL RELEASE	AB	JR	-



Client: **USCE EIREANN** Project No: **312**

Project Title: **LINK ROAD, CHAPELTOWN, CARLOW** DTM No: **001**

Drawing Title: **TM1001 - ROAD CLOSED** Revision: **D** Scale: **NTS**

